

# Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Printing Date: 10/20/2014

Revision: 10/20/2014

## Trade Name: E 100-PT-4™ Part B – Pigmented Epoxy

### 1 Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade Name: E 100-PT-4™ Part B

#### 1.2 Article No.: E100-PT-4™ Part B

#### 1.3 Details of the supplier of the Safety Data Sheet Manufacturer:

Elite Crete Systems  
 1151 Transport Drive  
 Valparaiso, IN 46383  
 Toll Free: 888.323.4445  
 Tel: (219) 465-7671  
 Fax: (219) 531-0898  
[www.elitecrete.com](http://www.elitecrete.com)

#### 1.4 Emergency telephone number:

CHEMTREC US DOMESTIC: (800-424-9300)  
 CHEMTREC INTERNATIONAL: (703-527-3887)

### 2 Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008 and GHS:

Reproductive Toxicity Category 2  
 Acute Inhalation Toxicity Category 4  
 Acute Oral Toxicity Category 4  
 Skin Sensitization Category 1  
 Skin Corrosion/Irritation Category 2  
 Acute Aquatic Toxicity Category 1  
 Chronic Aquatic Toxicity Category 2

##### Classification according to Directive 1999/45/EC:



C; Corrosive.

R34: Causes burns.



Xn; Harmful.

R22: harmful if swallowed.



Xi; Sensitizing.

R43: May cause sensitization by skin contact.



N; Dangerous for the environment

R50: Very toxic to aquatic organisms.

#### Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

#### Classification System:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

# Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Printing Date: 10/20/2014

Revision: 10/20/2014

## Trade Name: E 100-PT-4™ Part B – Pigmented Epoxy

### 2.2 Label elements

Labeling according to Regulation (EC) No 1272/2008:

Hazard pictograms:



GHS05 GHS07 GHS08 GHS09

Signal Word: Danger

Hazard-determining components of labeling: Contains Benzene-1,3-Dimethanamine, Trimethylhexane-1,6-Diamine

Hazard statements:

- H361: Suspected of damaging fertility or the unborn child.
- H302 Harmful if swallowed.
- H332: Harmful inhaled.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H400: Vary toxic to aquatic life.
- H401: Very toxic to aquatic life with long lasting effects.

Precautionary statements

- P260: Do not breath dust/fume/gas/mist/vapors/spray
- P264: Wash hands thoroughly after handling
- P270: Do not eat, drink or smoke when using this product
- P271: Use only in well ventilated area.
- P273: Avoid release to the Environment
- P280: Wear protective gloves/protective clothing/eye protection/face protection
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P370+P378: In case of fire: Use for extinction: CO2, powder or water spray.
- P302+P352: IF ON SKIN: Wash with plenty of soap and water.
- P391: Collect spillage.
- P403+P235: Store in a well-ventilated place. Keep cool.
- P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard description:


Canadian WHMIS Classification:

- D2B - Toxic material causing other toxic effects.
- E - Corrosive material

WHMIS-symbols:



NFPA ratings (scale 0 - 4)



Health = 3  
Fire = 1  
Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health	3
Fire	1
Reactivity	0

Health = 3  
Fire = 1  
Reactivity = 0

### 2.3 Other hazards

No known

# Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Printing Date: 10/20/2014

Revision: 10/20/2014

## Trade Name: E 100-PT-4™ Part B – Pigmented Epoxy

### 3 Composition/information on ingredients

#### 3.2 Mixture.

**Description:** Mixture of substances listed below with nonhazardous additives.

**Hazardous components:**

Identification #	Description	WT. %
CAS: 98-54-4 EINECS: 202-679-0	<b>Paratertiarybutyphenol</b> HAZARD CLASSIFICATION: [C] Corrosive. [N] Dangerous to the Environment RISK PHRASES: R34, R51/53	35 – 50%
CAS: 1477-55-0 EINECS: 216-032-5	<b>Benzene-1,3-dimethanamine</b> HAZARD CLASSIFICATION: [C] Corrosive RISK PHRASES: R34	20 – 30%
CAS: 25620-58-0 EINECS: 247-134-8	<b>Trimethylhexamethylenediamine</b> HAZARD CLASSIFICATION: [Xn] Harmful RISK PHRASES: R37, R43	25 – 45%
CAS: 25154-52-3 EINECS: 246-672-0	<b>Nonyl Phenol</b> HAZARD CLASSIFICATION: Repr Cat 3, [Xn] Harmful, [C] Corrosive, [N] Dangerous to the Environment RISK PHRASES: R22, R62, R63, R34, R50/53	1 – 5%
CAS: 135108-68-2 EINECS: NO DATA	<b>Methyleneoxide Polymer with benzeneamine Hydrogenated</b> HAZARD CLASSIFICATION: RISK PHRASES:	20-39%
CAS: 100-51-6	<b>Benzyl Alcohol</b> HAZARD CLASSIFICATION: RISK PHRASES:	5-30%

**Additional information:** Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).

### 4 First aid measures

#### 4.1 Description of first aid measures

##### After inhalation:

If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing difficulty continues.

##### After skin contact:

Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder contaminated clothing before re-use.

##### After eye contact:

If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation develops.

##### After swallowing:

If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

#### 4.2 Most important symptoms and effects, both acute and delayed.

**Acute:** This material is harmful if inhaled and may cause delayed lung injury. This material may cause irritation to the respiratory tract and skin and even burns. Product may cause an allergic skin reaction.

**Chronic:** Prolonged or repeated skin contact may cause dermatitis.

**Target Organs:** **Acute:** Eye, Respiratory System, Skin **Chronic:** Skin

**Hazards:** Pre-existing skin or respiratory system problems may be aggravated by exposure to this product.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Treat symptoms and reduce over-exposure.

# Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Printing Date: 10/20/2014

Revision: 10/20/2014

## Trade Name: E 100-PT-4™ Part B – Pigmented Epoxy

### 5 Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing agents:

Carbon dioxide, foam, dry chemical, halon, water spray, sand, limestone powder.

#### 5.2 Special hazards arising from the substance or mixture:

This product is flammable above flash point indicated above.

#### 5.3 Advice for firefighters:

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

### 6 Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures:** Personnel should be trained for spill response operations.

**6.2 Environmental precautions:** All work practices must be aimed at eliminating environmental contamination.

**6.3 Methods and material for containment and cleaning up:** Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up with a non-combustible absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

### 7 Handling and storage

#### 7.1 Precautions for safe handling

As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors/mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Storage:

##### Requirements to be met by storerooms and receptacles:

Store between 5° and 300C and avoid contact with skin and eyes. Do not store near acids. Ground all transfer equipment. Hold bulk storage under a nitrogen blanket. This product should not come in contact with copper or copper-bearing alloys. Containers of this product must be properly labeled. Nitrogen purging of containers is ideal and good practice.

**7.3 Specific end use(s):** No information

### 8 Exposure controls/personal protection

#### Additional information about design of technical facilities:

Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used.

#### 8.1 Control parameters

##### Ingredients with limit values that require monitoring at the workplace:

Currently, International exposure limits are not established for the components of this product. Please check with competent authority in each country for the most recent limits in place.

# Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Printing Date: 10/20/2014

Revision: 10/20/2014

## Trade Name: E 100-PT-4™ Part B – Pigmented Epoxy

### 8.2 Exposure controls

#### Personal protective equipment:

##### General protective and hygienic measures:

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

**Respiratory protection:** Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

**Protection of hands:** Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.



Protective gloves

##### Material of gloves:

The selection of suitable gloves does not only depend on the material, but also on the quality, and varies from manufacturer to manufacturer.

**Eye protection:** Safety glasses or chemical goggles as appropriate to prevent eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.



Safety goggles

##### Body Protection:

Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

## 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

##### Appearance:

**Form:**

Liquid

**Color:**

Translucent yellow or brown

**Odor:**

Mild epoxy odor

**Odor threshold:**

Not Available

**pH-value:**

Not Available

##### Change in condition

**Melting point/Melting range:**

No data available

**Boiling point/Boiling range:**

>446°F (230°C)

**Flash point:**

>392°F (>200°C)

**Flammability (solid, gaseous):**

No data available

**Auto/Self-ignition temperature:**

Not established

**Decomposition temperature:**

No data available

**Self-igniting:**

No data available

**Danger of explosion:**

This product is a flammable liquid above flash point shown above.

**Explosion limits**

**Lower:**

Not established

## Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Printing Date: 10/20/2014

Revision: 10/20/2014

### Trade Name: E 100-PT-4™ Part B – Pigmented Epoxy

<b>Upper:</b>	Not established
<b>Vapor pressure at 20 °C:</b>	<10.34 mmHg @ 21°C
<b>Density at 20°C:</b>	61.804 lb/ft <sup>3</sup> (0.99 g/cm <sup>3</sup> )@70°F (21°C)
<b>Relative density:</b>	8.10 pounds per gallon @ 25°C (SG 0.973)
<b>Vapor density:</b>	No data available
<b>Evaporation rate:</b>	No data available
<b>Solubility in / Miscibility with Water:</b>	Not Available
<b>Specific Gravity 20oC: (Water = 1):</b>	Not Available
<b>Viscosity:</b>	
<b>Dynamic:</b>	No data available
<b>Kinematic:</b>	No data available
<b>Solvent content:</b>	
<b>Organic solvents:</b>	No data available
<b>VOC (EC)</b>	0.00 VOC
<b>9.2 Other information</b>	No data available

## 10 Stability and reactivity

### 10.1 Reactivity

### 10.2 Chemical stability:

Product is stable  
**Thermal decomposition / conditions to be avoided:** When heated to decomposition this product produces noxious gases such as CO, CO<sub>2</sub>, NO<sub>x</sub>, amines, ammonia and others.

### 10.3 Possibility of hazardous reactions:

No data available

### 10.4 Conditions to avoid:

Contact with incompatible materials

### 10.5 Incompatible materials:

Oxidizing agents and amines should be avoided as these will cause exothermic polymerization. Avoid extreme heat

### 10.6 Hazardous decomposition products:

Will not occur

## 11 Toxicological information

### 11.1 Information on toxicological effects:

Toxicity data is available for this product

#### Acute toxicity:

Acute Dermal	LD 50	>2,000 mg/kg	Rabbit
Acute Oral	LD 50	1,750 mg/kg	Rat

**Primary irritant effect:** Contact with this product can be irritating to exposed skin, eyes and respiratory system.

**Sensitization:** This product is considered a skin sensitizer.

#### Additional toxicological information:

None of the ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore is not considered to be, nor suspected to be a cancer-causing agent by these agencies. CAS# 64742-53-6 is classified in the EU as a possible cancer causing material.

**Reproductive toxicity information:** No information concerning the effects of this product and its components on the human reproduction system.

## Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Printing Date: 10/20/2014

Revision: 10/20/2014

### Trade Name: E 100-PT-4™ Part B – Pigmented Epoxy

#### 12 Ecological information

##### 12.1 Toxicity

**Aquatic toxicity:** No data available

**12.2 Persistence and degradability:** No data available

**12.3 Bioaccumulative potential:** No data available

**12.4 Mobility in soil:** No evidence is currently available on this product's effects on plants or animals.

**Ecotoxicological effects:**

**Remark:**

**Additional ecological information:** No data available

**General notes:**

**Component Information:**

nonyl phenol CAS# 25154-52-3

Acute Fish Toxicity 96 hr LC50 0.13 mg/l fathead minnow (*Pimephales promelas*)

48 hr EC50 0.19 mg/l *Daphnia Magna*

Harmful to aquatic organisms. May cause long term damage to environment

#### 13 Disposal considerations

##### 13.1 Waste treatment methods

**Recommendations:**

Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

**RCRA WASTE CODE:** D002

**EU WASTE CODE:** To Be Established

#### 14 Transport information

##### 14.1 UN-Number

DOT: CAN: ADR: ADN: IMDG: IATA: **UN2735**

##### 14.2 UN proper shipping name

DOT: CAN: ADN: IMDG: IATA: **Amines, Liquid, Corrosive, N.O.S. (Contains Benzene-1,3-Dimethanamine, Trimethylhexane-1,6-Diamine)**

ADR

**2735 Amines, Liquid, Corrosive, N.O.S. (Contains Benzene-1,3-Dimethanamine, Trimethylhexane-1,6-Diamine)**

##### 14.3 Transport hazard class(es)

DOT: CAN: ADN: IMDG: IATA:

**CLASS:**

**8 corrosive substances**

**LABELS:**



##### 14.3 Transport hazard class(es)

ADR

**CLASS:**

**8 (C7) Corrosive substances**

**LABELS:**




## Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Printing Date: 10/20/2014

Revision: 10/20/2014

### Trade Name: E 100-PT-4™ Part B – Pigmented Epoxy

<b>14.4 Packing group</b> DOT, ADR, IMDG, IATA:TGD	<b>PG II</b>
<b>14.5 Environmental hazards:</b> <b>Marine pollutant:</b>	Yes
Special markings (ADR)	
<b>14.6 Special precautions for user</b> <b>Danger code (Kemler):</b> <b>EMS Number:</b>	Warning corrosive substances 80 F-A,S-B
<b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:</b>	No data available
<b>Transport/Additional information</b> <b>ADR</b> <b>Limited Quantities (LQ)</b> <b>Excepted Quantities (EQ)</b>	5L Code: E1 Maximum net quantity per inner packaging 30ml Maximum net quantity per outer packaging 1000 ml
<b>Transport Category:</b> <b>Tunnel restriction code:</b>	3 E
<b>UN "Model Regulation":</b>	UN2735 Amines, Liquid, Corrosive, N.O.S. (Contains Benzene-1,3-Dimethanamine, Trimethylhexane-1,6-Diamine), Marine Pollutant, Class 8, PGII

### 15 Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture. United States (USA)

**SARA:** This product is not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act.: None

**Section 355 (extremely hazardous substances):** None of the ingredients are listed.

**Section 313 (Toxic Release Inventory):** None of the ingredients are listed.

**TSCA (Toxic Substances Control Act):** All ingredients are listed.

#### Proposition 65 (California):

##### Chemicals known to cause cancer:

None of the ingredients is listed.

#### Canada

##### Canadian Domestic Substances List (DSL):

All ingredients are listed

##### Canadian Ingredient Disclosure list (limit 0.1%):

None of the ingredients are listed.

##### Canadian Ingredient Disclosure list (limit 1%):

None of the ingredients are listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.



## Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Printing Date: 10/20/2014

Revision: 10/20/2014

### Trade Name: E 100-PT-4™ Part B – Pigmented Epoxy

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

##### **Hazard statements:**

- H361: Suspected of damaging fertility or the unborn child.
- H302 Harmful if swallowed.
- H332: Harmful inhaled.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H400: Vary toxic to aquatic life.
- H401: Very toxic to aquatic life with long lasting effects.

##### **Precautionary statements**

- P260: Do not breath dust/fume/gas/mist/vapors/spray
- P264: Wash hands thoroughly after handling
- P270: Do not eat, drink or smoke when using this product
- P271: Use only in well ventilated area.
- P273: Avoid release to the Environment
- P280: Wear protective gloves/protective clothing/eye protection/face protection
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P370+P378: In case of fire: Use for extinction: CO2, powder or water spray.
- P302+P352: IF ON SKIN: Wash with plenty of soap and water.
- P391: Collect spillage.
- P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

##### **Abbreviations and acronyms:**

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation.
- IATA: International Air Transport Association.
- ACGIH: American Conference of Governmental Industrial Hygienists.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- NFPA: National Fire Protection Association (USA).
- HMIS: Hazardous Materials Identification System (USA).
- LC50: Lethal concentration, 50 percent.
- LD50: Lethal dose, 50 percent.